

Diamond Face Slab



An Updated Classic

Barkman's newly updated Diamondface Slab is a great option for quickly laying down pathways or utility pads at a job site or in your own backyard. The thickness of each size has been increased to 2 inches and the surface texture has been significantly improved upon, resulting in a product that is more durable than its predecessor.



Paths




Patios


SIZES (L X W X H)



610 x 762 x 51 mm
24 x 30 x 2 in



610 x 610 x 51 mm
24 x 24 x 2 in




457 x 457 x 51 mm
18 x 18 x 2 in

COLOURS




Natural

PATTERNS



Pattern 1



Pattern 2

INSTALLATION NOTES

Barkman recommends the use of polymeric sand for commercial applications. A plate compactor should be used over the entire surface following installation.

For more in depth installation guides for specific products, visit BarkmanConcrete.com.

BUNDLE CONFIGURATIONS

DESCRIPTION	UNIT					PALLET				
	SIZE (L X W X H)		FACE AREA		WEIGHT	NO. OF UNITS	NO. OF ROWS	FACE AREA		WEIGHT
	MM	IN	M ²	SQ FT	LB			M ²	SQ FT	LB
18 x 18	457 x 457 x 51	18 x 18 x 2	.21	2.25	54	40	-	8.36	90	2160
24 x 24	610 x 610 x 51	24 x 24 x 2	.37	4	96	20	-	7.43	80	1920
24 x 30	610 x 762 x 51	24 x 30 x 2	.46	5	120	20	-	9.29	100	2400

Steinbach Office

152 Brandt Street
Steinbach, MB R5G 0R2
T (800)-461-2278
F (204)-326-5915

Winnipeg Office

901 Gateway Road
Winnipeg, MB R2K 3L1
T (800)-342-2879
F (204)-663-4854

Vancouver Office

2104-290 Newport Drive
Port Moody, BC V3H 5N2
T (778)-689-7670
F (604)-949-0321

Calgary Office

813 McCool St. Box 1136
Crossfield, AB T0M 0S0
T (403)-946-4630
F (403)-946-4631

